

# PRODUCT DATA SHEET

## M-Protect™

### RELEASE AGENT FOR EASIER CLEANING OF CONCRETE POLISHING, CUTTING AND TROWELING MACHINES

M-Protect™ is a release agent, which is sprayed onto grinding or cutting machines prior to each usage. With M-Protect™, dried concrete and limestone slurry sticks less and is easier to clean off at the end of the day.

#### How to Use

Clean machine/s and tools first.

Apply a very thin layer on your clean machine surfaces, using a pump sprayer with the nozzle set to a very fine spray.

#### Precautions

Use safety goggles and respirator when applying.

Avoid ingestion and prolonged or repeated contact with skin. If contact with eyes occurs, wash eyes with copious quantities of water and consult doctor if irritation persists. All relevant information is provided within the Material Safety Data Sheet.

#### First Aid

If contact with eyes occurs, wash eyes with copious quantities of water and consult doctor if irritation persists.

If ingested (swallowed) DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

For advice, immediately contact a doctor, ambulance, or, a Poison Information Centre:

**Australia** - 13 11 26 (Australia Wide)

**USA - American Association of Poison Control Centres** 1-800-222-1222

**Canadian Poison Centres** – Ontario (24/7): Telephone: 416-813-5900; Toll free: 1-800-268-9017

**UK - England and Wales:** NHS 111 - dial 111; **Scotland:** NHS 24 - dial 111; **Republic of Ireland:** 01 809 2166

#### Accidents

- Spillage – Take up mechanically or with absorbent material such as sand, earth or vermiculite.

#### Transport

- TDG UN Status: This material is not regulated hazardous material for transportation.

#### Pack Sizes

# PRODUCT DATA SHEET

- 1L (1.06Q); 5L (1.3G); 30L (5.3G)

## Shelf Life and Storage Guidelines

- Shelf life is 24 months from the date of delivery.
- Storage temperature should be within the range of 5 to 32°C (40-90°F)
- Containers should be well sealed.

## Technical Data

- Specific Gravity: ~0.89
- Viscosity: maximum 250cps at 20°C
- Colour: straw coloured
- Weight: 1L (1.06Q) = 0.92Kg (2Lb.); 5L (1.3G) = 4.8Kg (10.6Lb), 20L (5.3G) = 18.2Kg (40Lb)
- VOCs: Zero

**Country of Manufacture:** Australia