



READY-TO-USE, ADVANCED ACID WASH FOR QUICK REMOVAL OF DRIED CONCRETE / LIMESTONE SLURRY FROM MACHINES, TOOLS & FORMWORK

- Ready to use formulation
- Easier cleaning of dried cement/stone slurry from machinery/tools
- Small molecule size & superior wetting properties for maximum penetration
- Ideal for cleaning dried concrete off metal/wood formwork, laser screeds, power trowels, truss screeds, buckets, buggies, conveyors, boom pumps, line pumps, truck mount pumps, hand tools

How To Use

1. Test on an inconspicuous area and allow to dry and then check result.
2. Use a standard plastic low pressure pumper sprayer.
3. Spray M-Clean™ on uniformly.
4. Leave the product to work for 5-30 minutes.
5. NOTE: Multiple applications may be required if you have a lot of concrete residue to remove.
6. Rinse treated area with a hose or preferably a pressure washer.

Warnings

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Precautions

- Wear protective gloves / protective clothing / eye protection / face protection.
- Avoid breathing dust / fume / gas / mist / vapours / spray.
- Wash thoroughly after handling
- Use only outdoors or in a well-ventilated area

First Aid

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Skin contact	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre or a doctor (at once). If swallowed, do not induce vomiting.

Technical Data

- Specific Gravity: 1.05
- Colour: Light tan clear liquid
- Weight: 5 L (1.3 gal) = 5.5 kg (12.13 lb), 20L (5.3 gal) = 22 kg (48.5 lb)

Transport

Not classified as a dangerous good by the criteria of the ADG Code, IMDG or IATA

Pack Sizes

5 L (1.3 gal); 20L (5.3 gal)

Shelf Life and Storage Guidelines

Best within 3 years of manufacture date. Store away from direct sunlight. Keep container tightly sealed, in a well-ventilated place, at 2 - 32 °C/36 - 90 °F.

Manufactured In Australia

16 Westside Drive, Laverton North, VIC, Australia, 3020.
Emergency Tel +61 (0)417 339 927
info@chemforce.com.au
www.chemforce.com.au

