

# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

**Product name** CHEMFORCE STAIN PROTECTOR

**Synonyms**

### 1.2 Uses and uses advised against

**Uses** STONE AND MASONRY IMPREGNATING SEALER  
Water and oil repellent for protecting stone, concrete and masonry.

### 1.3 Details of the supplier of the product

**Supplier name** CHEMFORCE PTY LTD.  
**Address** 16 Westside Drive, Laverton North, VIC, 3026, AUSTRALIA  
**Telephone** +61 (0)417 339 927  
**Email** [john@chemforce.com.au](mailto:john@chemforce.com.au)  
**Website** <http://www.chemforce.com.au>

### 1.4 Emergency telephone numbers

**Emergency** +61 (0)417 339 927

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### Physical Hazards

Flammable Liquids: Category 2

#### Health Hazards

Serious Eye Damage / Eye Irritation: Category 2A

#### Environmental Hazards

Not classified as an Environmental Hazard

### 2.2 GHS Label elements

**Signal word** DANGER

**Pictograms**



#### Hazard statements

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.

#### Prevention statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

## PRODUCT NAME CHEMFORCE STAIN PROTECTOR

### Response statements

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P370 + P378 In case of fire: Use appropriate media to extinguish.

### Storage statements

P403 + P235 Store in a well-ventilated place. Keep cool.

### Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

### 2.3 Other hazards

No information provided.

---

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

---

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ALKYL ALKOXY SILANE	-	-	30 to 60%
ETHANOL	64-17-5	200-578-6	30 to 60%
N-BUTYL ACETATE	123-86-4	204-658-1	1 to <10%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

---

## 4. FIRST AID MEASURES

---

### 4.1 Description of first aid measures

**Eye** If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

**First aid facilities** Eye wash facilities and normal washroom facilities should be available.

### 4.2 Most important symptoms and effects, both acute and delayed

Chronic exposure may result in cirrhosis of the liver. Over exposure may result in central nervous system (CNS) depression, with nausea, dizziness and unconsciousness at high levels.

### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

---

## 5. FIRE FIGHTING MEASURES

---

### 5.1 Extinguishing media

Water fog or foam. Prevent contamination of drains and waterways.

### 5.2 Special hazards arising from the substance or mixture

Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

### 5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**5.4 Hazchem code**

- 3YE
- 3 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

**7. HANDLING AND STORAGE**

---

**7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems.

**7.3 Specific end uses**

No information provided.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**8.1 Control parameters****Exposure standards**

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Butyl acetate	SWA [Proposed]	50	270	200	950
Ethanol	SWA [AUS]	1000	1880	--	--
Ethanol (Ethyl alcohol)	SWA [Proposed]	200	380	800	1500
n-Butyl acetate	SWA [AUS]	150	713	200	950

**Biological limits**

No biological limit values have been entered for this product.

**8.2 Exposure controls****Engineering controls**

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

## PRODUCT NAME CHEMFORCE STAIN PROTECTOR

### PPE

<b>Eye / Face</b>	Wear splash-proof goggles.
<b>Hands</b>	Wear nitrile or neoprene gloves.
<b>Body</b>	When using large quantities or where heavy contamination is likely, wear coveralls.
<b>Respiratory</b>	Where an inhalation risk exists, wear a Type A (organic vapour) / Organic vapour respirator.



---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	CLEAR COLOURLESS TO STRAW YELLOW LIQUID
<b>Odour</b>	SWEET ODOUR
<b>Flammability</b>	HIGHLY FLAMMABLE
<b>Flash point</b>	< 23°C
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Vapour density</b>	NOT AVAILABLE
<b>Relative density</b>	0.84
<b>Solubility (water)</b>	NOT AVAILABLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	19 % (Ethanol)
<b>Lower explosion limit</b>	3.3 % (Ethanol)
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

---

## 10. STABILITY AND REACTIVITY

---

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

### 10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

---

## 11. TOXICOLOGICAL INFORMATION

---

### 11.1 Information on toxicological effects

**PRODUCT NAME CHEMFORCE STAIN PROTECTOR****Acute toxicity** May be harmful if swallowed in large quantities.**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL	3450 mg/kg (mouse)	--	20000 ppm/10 hours (rat)
N-BUTYL ACETATE	10760 mg/kg (rat)	14112 mg/kg (rabbit)	> 21 mg/L/4hrs (rat)

<b>Skin</b>	Contact may result in drying and defatting of the skin, rash and dermatitis.
<b>Eye</b>	Causes serious eye irritation. Contact may result in irritation, lacrimation, pain and redness.
<b>Sensitisation</b>	Not classified as causing skin or respiratory sensitisation.
<b>Mutagenicity</b>	Not classified as a mutagen.
<b>Carcinogenicity</b>	Not classified as a carcinogen.
<b>Reproductive</b>	Not classified as a reproductive toxin.
<b>STOT - single exposure</b>	Over exposure may result in central nervous system (CNS) depression, with nausea, dizziness and unconsciousness at high levels.
<b>STOT - repeated exposure</b>	Not classified as causing organ damage from repeated exposure. However, repeated oral overexposure to ethanol may result in cirrhosis of the liver.
<b>Aspiration</b>	Not classified as causing aspiration.

---

**12. ECOLOGICAL INFORMATION**

---

**12.1 Toxicity**

At low concentrations and amounts, ethanol is rapidly metabolised without apparent harm.

**12.2 Persistence and degradability**

Ethanol will oxidise quickly (less than a few days), with carbon dioxide and water as the final products. Ethanol present in soil or water will decompose in the presence of oxygen.

**12.3 Bioaccumulative potential**

Ethanol is not expected to bioconcentrate.

**12.4 Mobility in soil**

Ethanol is carried in the water and air. It is soluble in water and is volatile, so it can be carried quite long distances.

**12.5 Other adverse effects**

Avoid contamination of drains and waterways.

---

**13. DISPOSAL CONSIDERATIONS**

---

**13.1 Waste treatment methods**

**Waste disposal** For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

**Legislation** Dispose of in accordance with relevant local legislation.

---

**14. TRANSPORT INFORMATION**

---

**CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE**

**PRODUCT NAME CHEMFORCE STAIN PROTECTOR**

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	1993	1993	1993
<b>14.2 Proper Shipping Name</b>	FLAMMABLE LIQUID, N.O.S. (contains ethanol)	FLAMMABLE LIQUID, N.O.S. (contains ethanol)	FLAMMABLE LIQUID, N.O.S. (contains ethanol)
<b>14.3 Transport hazard class</b>	3	3	3
<b>14.4 Packing Group</b>	II	II	II

**14.5 Environmental hazards**

Not a Marine Pollutant.

**14.6 Special precautions for user**

<b>Hazchem code</b>	●3YE
<b>GTEPG</b>	3A1
<b>EmS</b>	F-E, S-E

---

**15. REGULATORY INFORMATION**

---

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

<b>Poison schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
<b>Classifications</b>	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
<b>Inventory listings</b>	<b>AUSTRALIA: AICC (Australian Inventory of Industrial Chemicals)</b> All components are listed on AICC, or are exempt.

---

**16. OTHER INFORMATION**

---

<b>Additional information</b>	<b>PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:</b> The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.
-------------------------------	--

**HEALTH EFFECTS FROM EXPOSURE:**  
It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**PRODUCT NAME    CHEMFORCE STAIN PROTECTOR**

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmtglobal.com](mailto:info@rmtglobal.com)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**